

WARRANTY TERMS

The guarantee of CICOGNANI ENGINEERING products is two years from the purchase data except for the parts subject to wear and tear from the switches, buttons, relays that is one year. The thermionic valves, indicator lights, wiring cables are guaranteed for three months. Security is not a problem, but it's just a way of thinking, managing things to do and not thinking about presented to the carrier); damage from incorrect connections, with non-conforming modifications (altered / modified), with interfacing to malfunctioning devices.

The responsibility of CICOGNANI ENGINEERING is limited to repairing the product or replacing it. (Replacement at our choice)

CICOGNANI ENGINEERING will not be liable for damages resulting from failure to use the product, interrupted operation, commercial, incidental, consequential, transport or unsuitable packaging.

How to receive assistance: Send an email request to project@cicognani.eu in order to make agreements on how and where to send the product. The product must be sent together with a copy of the receipt / sales receipt together with which a description of the claimed fault is appreciated. I recommend to make a packaging suitable to well protect the product not including manuals, cables, effects or various accessories. The costs of labor and material under warranty will be charged to the CICOGNANI ENGINEERING.

Shipping and packing costs are the responsibility of the purchaser.

THE WARRANTY HAS VALIDITY IF THE PRODUCT IS A COPY OF THE RECEIPT OF SALE IN A WAY THAT ATTEND THE DATE OF PURCHASE



1959 TIMEDRIVE

CICOGNANI BOUTIQUE SERIE



USER MANUAL

(UK)

CICOGNANI ENGINEERING

Via Faentina, 44 - 48013 - Brisighella (RA) Italy
Internet: www.cicognani.eu Mail: project@cicognani.eu
P.iva: 01277580393

USEFUL INFORMATION

1959 TIMEDRIVE is an overdrive pedal designed for "old tone style" distortions. Ideal for use as both a signal boost and an overdrive. The characteristic that distinguishes it is the faithful saturation typical of the most famous British amplifiers combined with an impact signal dynamics. The dual power circuit increases performance to the point of providing excellent touch benefits with an amazing sound definition. Inspired by the "British sound" 1959 TIMEDRIVE ranges from low to mid-level gain while maintaining a pleasant feeling like that of historical amplifiers played at high volume

Active tone control sculpting sound effectively allowing you to easily find the sound we have in mind.

The input stage with parallel double buffer magically adapts the input impedance is if you enter with the guitar (High impedance) or in series with effects pedal, (low impedance) example, boost or overdrive.

The Guru advises:

- 1) Use good quality signal cables.
- 2) Avoid in case of connections with metal angle jacks that the body of the same is touched with that of the near pedals.
- 3) The power is very important. Connect the unit to a power supply able to supply a stabilized voltage between 9 and 12VDC with a current of at least 100mA in order to obtain the correct performances.
- 4) The pedal has a true-bypass switch so as not to contaminate the sound in case "not active". It is therefore not necessary to use miraculous buffers upstream or downstream of 1959 TIMEDRIVE.

CAUTION!! Make sure to check the power supply connection as per technical specifications from 9 to 12VDC (**negative tip**).

The product is designed to be powered from outside. Do not open the plate below it is not designed for any battery.

TECHNICAL FEATURES

POWER IN	9 TO 12VDC(NEGATIVE TIP)
CONSUMPTION	MAX 40mA TO 12VDC
INPUT IMPEDENCE	< 1 M Ohm
INPUT LEVEL	MAX 500mV
BASS FREQUENCY	110 Hz
MIDDLE FREQUENCY	680 Hz
TREBLE FREQUENCY	4500 Hz
MAX S/N RATIO	58db
MAX GAIN	+60db
WEIGHT	0,3 Kg. (0,6 lib.)
WIDTH	94 mm. (3,7 in.)
LENGHT	120 mm. (4,7 in.)
HEIGHT (MAX)	45 mm. (1,770 in.)